

### KA-10R

#### Wireless Camera Receiver

The KA-10 system includes KA-10R, KA-10T, KAC50X / KAC150 cable, TG-10CH2, shoe mount adapter, and CM-201 microphone. It is designed for both professional and consumer video camera. The CM-201 provides omni directional pick up pattern to expand the coverage to make a meeting.

- \* Lithium battery can go for 14 hours which is useful for travel.
- \* UHF PLL 16 selectable frequency can render multi system application.
- \* Over 60 meter operation distance virtually meets all kinds of application.

**Frequency Preparation:** PLL Synthesized Control  
**Carrier Frequency Range:** 502 ~ 960 MHz  
**LED Display:** Channel  
**Controls:** Power On / Off, Channel selection, Volume control  
**Audio Frequency Response:** 40 ~ 18,000 Hz  
**Output connector:** 1/8 "Dummy stereo Phone Jack  
**Battery life:** 14 hours typical  
**Battery:** Lithium cell (3.7V, 1300mAh)  
**Dimension (mm):** 54mm(W)\* 17mm(D)\* 99mm(H)



KA-10R

KA-10T

### KA-10T

#### Wireless Camera Transmitter

**Internal Microphone:** Omni-directional Condenser Microphone  
**Frequency Preparation:** PLL Synthesized Control  
**Carrier Frequency Range:** 502 ~ 960 MHz  
**RF Outputs:** 10mW  
**Stability:** ± 10kHz  
**Frequency Deviation:** ± 48kHz  
**LED Display:** Channel  
**Controls:** Power On / Off, Channel selection, Volume control  
**Spurious Emissions:** <-50 DBC  
**Audio Frequency Response:** 40 ~ 18,000 Hz  
**Microphone input connector:** 1/8 "Mono Phone Jack  
**Battery life:** 14 hours typical  
**Battery:** Lithium cell (3.7V, 1300mAh)  
**Dimension (mm):** 54mm(W)\* 17mm(D)\* 99mm(H)

### KA-8TH

#### UHF PLL Handheld Transmitter

**Frequency Preparation:** PLL Synthesized Control  
**Channel number:** 16  
**Carrier Frequency Range:** 502 ~ 960 MHz  
**RF Outputs:** 10mW  
**Stability:** ± 10kHz  
**Frequency Deviation:** ± 48kHz  
**LED Display:** Channel  
**Controls:** Power On / Off, Channel Up / Down, Mute  
**Spurious Emissions:** <-50 DBC  
**Audio Frequency Response:** 40 ~ 16,500 Hz  
**Battery:** UM3, AA 1.5V \* 2

### Mh-16TG

#### UHF PLL Handheld Transmitter

**Frequency Preparation:** PLL Synthesized Control  
**Channel number:** 16  
**Carrier Frequency Range:** 502 ~ 960 MHz  
**RF Outputs:** 10mW  
**Stability:** ± 10kHz  
**Frequency Deviation:** ± 48kHz  
**LED Display:** Channel  
**Controls:** Power On / Off, Channel Up / Down, Mute  
**Spurious Emissions:** <-50 DBC  
**Audio Frequency Response:** 50 ~ 16,000 Hz  
**Battery:** UM3, AA 1.5V \* 2



KA-8TH  
Option

Mh-16TG  
Option



KAC50X  
Camera Cable



KAC150  
Camera Cable



KA-Y Cable  
Camera Cable  
Option



SMA-10  
Shoe Mount Adapter



CM-201B / CM-201F  
Miniature Lavalier Microphone



TG-10CH2   
2-Slot Charger

### TG-98RA/TG-98TA

#### Wireless Camera Receiver / Transmitter

- \* TG-98 is a wide band wireless microphone system for video camera with 36 Mhz.
- \* Preset 6 groups each of up to 23 channels.
- \* Maximum operation distance 200 meters with antenna version and at 20 mW RF output.
- \* Transmission power selectable
- \* Built in microphone at Transmitter.
- \* RF Strength gauge
- \* Panel lock provided
- \* Line out level adjustable
- \* Necessary accessories are bundled.

**Frequency Preparation:** PLL Synthesized Control  
**Carrier Frequency Range:** 502 ~ 960 MHz  
**Controls:** Channel Power On / Off, Channel selection Volume control, Group selection, Limiter  
**Audio Frequency Response:** 40 ~ 18,000 Hz  
**Output connector:** 1/8 "Dummy stereo Phone Jack  
**Battery life:** 10 hours typical  
**Battery:** Rechargeable NIMH AA (1.2V, 2000mAh)  
**Dimension (mm):** 62mm(W)\* 22mm(D)\* 112mm(H)



TG-98RA

TG-98TA

### TX-966K

#### UHF PLL Handheld Transmitter

- \* All new D-36 capsule provides maximum gain before feedback
- \* 36MHz wide band
- \* Phase-locked Loop (PLL) synthesized tuner.
- \* Adjustable transmission power between Low / High
- \* GAIN control -9,-6,-3,0,+3,+6,+9,+12dB
- \* Lock-on function
- \* Frequency and channel are both adjustable

**Frequency Preparation:** PLL Synthesized Control  
**Carrier Frequency Range:** 502 ~ 960 MHz  
**RF Outputs:** Lo / High  
**Stability:** ± 10KHz  
**Frequency Deviation:** ± 48KHz  
**LCD Display:** Preset channel, Battery Fuel Gauge, Frequency  
**Controls:** Power On / Off, Frequency Up / Down, Lock-on Mode, Preset channel, A or B channel select, RF outputs adjust, Gain control  
**Spurious Emissions:** <-50 DBC  
**Audio Frequency Response:** 50 ~ 16,000 Hz  
**Battery:** UM3, AA 1.5V \* 2



TX-966K





### KAC50X / KAC150

Camera Cable



### SMA-64

Shoe Mount Adapter



### KA-Y Cable Option

Camera Cable



### CM-201B / CM-201F

Miniature Lavalier Microphone



### KA-21 carry case P-110 Option

The KA-21 can contain two body pack receiver.



### TG-64CH2 P-54 Option

2-Slot Charger



### KA-21 kit

This kit includes 1 x KA-21 and 1 x KA-Ycable for two receivers working with one camera.



## Wireless Tour Guide System

The TG-series Tour Guide System provides listening assistance to not only tourists but also to all people who needs to choose a source or a language from the many.

