

Condenser Gooseneck Microphones

MAIN FEATURES

- Gooseneck with integrated 3-pin XLR male plug
- Minimum susceptibility to acoustic feedback
- LED for indicating operating status
- Include foam windscreen

DESCRIPTION

The GM Series Condenser Gooseneck Microphones are available in 3 versions: The GM-5206, GM-5212, GM-5218; and are terminated with an XLR(M) plug connector for mating to an XLR(F) connector.

- Definitive polar pattern allows for demanding sound pickup applications.
- The small diameter gooseneck design permits flexible positioning.
- High sensitivity allows for quality sound pickup under difficult conditions.
- Equipped with XLR connector.
- Foam Windscreen provided for shielding against wind noise and "popping".



TECHNICAL SPECIFICATIONS

GENERAL	GM 5206L	GM 5212L	GM 5218L
Code	27515	27514	27513
Directivity	Cardioid		

ACOUSTIC SPECIFICATIONS

Frequency response	80 Hz ÷ 18kHz
Sensitivity (@1kHz)	- 60dB
Output impedance	220Ohm
MAX SPL	125dB

POWER SUPPLY - 36 ÷ 52Vdc

Output connector	XLR
------------------	-----

MECHANICAL SPECIFICATIONS

Material	Metal body		
Net dimensions (WxH)	152mm	305mm	457mm
	5.98inch	12inch	18inch
Net weight	0.14 kg	0.19 kg	0.25 kg
	0.30 lb	0.41 lb	0.55 lb

DIMENSIONAL DRAWING

